

BLANK PAGE



Indian Standard SPECIFICATION FOR SERVICE NAMEPLATES FOR MARINE VALVES AND FITTINGS

(First Reprint FEBRUARY 1986)

UDC 621-777:621.646.2:629.12



@ Copyright 1973

INDIAN STANDARDS INSTITUTION MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Indian Standard SPECIFICATION FOR SERVICE NAMEPLATES FOR MARINE VALVES AND FITTINGS

Shipbuilding Sectional Committee, MCPD 1

Chairman

SHRI S. PARMANANDHAN

Members

CDR S. P. AGARWALA

SHRI N. BALASUBRAMANIAM SHRI R. S. MITAL (Alternate)

SHRI D. P. BHATIA

SHRI Z. M. BHATE (Alternate)

SHRI A. S. BONDALE

SHRI N. CHAKRABORTY

SHRI S. RAGHAVAN (Alternate) CHIEF MECHANICAL ENGINEER, THE COMMISSIONERS FOR THE

PORT OF CALCUTTA

CHIEF MECHANICAL ENGINEER,

BOMBAY PORT TRUST (Alternate)

SHRI P. L. D'ABREO SHRI R. A. KAMATH (Alternate)

SHRI V. G. DAMLE

SHRI R. D. PARALKAR (Alternate)

SHRI B. HILL

SHRI D. B. IRANI SHRI T. R. VENKATESAWARAN (Alternate)

SHRI P. C. KUMAR

SHRI G. K. KURIYAN
SHRI M. VELU (Alternate)

SHRI KJELL LINDH SHRI G. SINHA (Alternate)

SHRI S. MAJUMDAR

SHRI K. N. G. MENON CAPT R. D. KOHLI (Alternate)

SHRI I. N. PRADHAN

SHRI T. S. RAJAN REPRESENTATIVE

DR M. K. GHOSH ROY

Representing

Ministry of Defence (NHQ)

Ministry of Defence (DGI) Voltas Ltd, Bombay

Mukand Iron & Steel Works Ltd, Bombay

Garden Reach Workshops Ltd, Calcutta Ministry of Parliamentary Affairs, Shipping & Transport

Inter Port Consultation Secretariat Cell, Calcutta

Kamath & D'Abreo, Cochin

AFCO Ltd, Bombay

DIRECTOR OF NAVAL CONSTRUCTION Ministry of Defence (NHQ)

Lloyd's Register of Shipping, Calcutta

Cochin Shipyard Project, Cochin

Institute of Marine Engineers, Bombay Central Institute of Fisheries Technology, Cochin

SF India Ltd, Calcutta

Directorate General of Technical Development, New Delhi

Shipping Corporation of India Ltd, Bombay

Indian National Shipowners' Association, Bombay Ericson & Richards, Bombay

Indian Engineering Association, Bombay

Directorate General of Shipping (Ministry of Parliamentary Affairs, Shipping & Transport)

(Continued on page 2)

INDIAN STANDARDS INSTITUTION MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG **NEW DELHI**

IS: 6645 - 1972

(Continued from page 1)

Members

Representing

SHRI ANJAN ROVE
SHRI E. R. DASTOOR (Alternate)
SHRI K. N. G. MENON (Alternate)
SHRI S. G. SCHAEFFER
SHRI K. SHARMA (Alternate)
SHRI D. S. SHETH
SHRI M. G. KUTTY (Alternate)
SHRI T. N. SUJAN
SHRI K. S. SUBRAMANIAM.
Larsen & Toubro Ltd, Bombay
Director General, ISI (Ex-officio Member)

Marine Piping Subcommittee, MCPD 1:1

Convener

SHRI D. S. SHETH

(Secretary)

Hindustan Shipyard Ltd, Visakhapatnam

Members

SHRI S. SRINIVASAN (Alternate to

Officer on Special Duty (MCPD)

Shri D. S. Sheth) Shri A. S. Bondale

DIRECTOR OF NAVAL CONSTRUCTION

SHRI P. L. RAO

DR M. K. GHOSH ROY

SHRI D. K. SEHGAL

SHRI V. K. PURI (Alternate)
SHRI M. P. SUNDARBSAN

SHRI M. P. SUNDARESA!
SHRI J. M. TRINDADE

Garden Reach Workshops Ltd, Calcutta Ministry of Defence (NHQ)

Inter Port Consultation Secretariat Cell, Calcutta Directorate General of Shipping (Ministry of Parliamentary Affairs, Shipping & Transport)

Leader Engineering Works, Jullundur

Indian Tube Co Ltd, Jamshedpur

Rajabagan Dockyard of Central Inland Water Transport Corporation Ltd, Calcutta

Indian Standard SPECIFICATION FOR SERVICE NAMEPLATES FOR MARINE VALVES AND FITTINGS

0. FOREWORD

- 0.1 This Indian Standard was adopted by the Indian Standards Institution on 28 July 1972, after the draft finalized by the Shipbuilding Sectional Committee had been approved by the Marine, Cargo Movement and Packaging Division Council.
- **0.2** A large number of valves of various types are used on board ships. For easy identification and operation, it is essential that the correct name-plates are fitted to each of the valves.
- **0.3** For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS:2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

- 1.1 This standard specifies the dimensions, material, inscription, manufacture and finish and general requirements of nameplates.
- 1.2 It is recommended that nameplates be used, wherever possible, on valves intended for marine duty.

2. TYPES

- 2.1 The nameplates shall be of two types, namely:
 - Type A circular nameplates generally used on valves with their handwheels fixed to the stem, and
 - Type B rectangular nameplates generally used on valves where it is impractical to use the Type A and also on other fittings.

^{*}Rules for rounding off numerical values (revised).

IS: 6645 - 1972


3. DIMENSIONS

- 3.1 The dimensions of Type A and Type B nameplates shall conform to Tables 1 and 2 respectively.
- 3.2 Types A and B nameplates shall have a thickness of 2 mm.

TABLE 1 DIMENSIONS OF CIRCULAR NAMEPLATES, TYPE A

(Clauses 3.1 and 5.4)

All dimensions in millimetres.



Diameter of Nameplate	Height of Letters	Approx No. of Combined Letters and Spaces	G	Bore of Valve
40 .	6	16	3	15 to 40
50	6	21	5	50 ,, 100
65	6	20	5	125 ,, 150
75	6	2 6	5	200 ,, 300
90	6	23	6	350 and over

Note — A 5 mm diameter hole is to be drilled in the centre of the nameplate by the manufacturer, unless otherwise specified.

4. MATERIAL

4.1 Nameplates shall be of any one of the following materials:

Aluminium

IS: 737-1965*

Brass

IS: 410-1967†

^{*}Specification for wrought aluminium and aluminium alloys, sheet and strip (for general engineering purposes) (revised).

[†]Specification for rolled brass plate, sheet, strip and foil (second revision).


Polystyrene
PVC sheets
Steel

IS:5210-1969*
IS:6307-1971†
IS:4759-1968‡

TABLE 2 DIMENSIONS OF RECTANGULAR NAMEPLATES, TYPE B

(Clauses 3.1 and 5.4)

All dimensions in millimetres.



Width of Nameplate A	HEIGHT OF LETTERS B	Approx No. of Combined Letters and Spaces		
		Single Line	Double Line	
15	6	10	- · · · -	
2 5	6	10	20	

Note - Single line inscription to be centrally located.

5. INSCRIPTION

- 5.1 The minimum size of engraving shall be 6 mm in height.
- 5.2 The minimum depth of engraving shall be 0.5 mm.
- 5.3 Lettering shall be clearly legible and of 'sans serif' upper case type.
- 5.4 The total number of letters and included spaces should not normally exceed that given in Tables 1 and 2.
- 5.5 Care should be exercised in the use of abbreviated expressions to ensure correct interpretation, and this applies especially when the instructions shall be in a foreign language.

^{*}Specification for high impact polystyrene sheet.

[†]Specification for PVC rigid sheet.

[†]Specification for hot-dip zinc coatings on structural sheet and other allied products.

IS: 6645 - 1972

5.6 The engraved letters shall be filled with black wax unless otherwise specified by the purchaser.

6. MANUFACTURE AND FINISH

- 6.1 The nameplates shall be flat and truly circular or rectangular depending on the type specified.
- 6.2 The centre hole, where provided in circular nameplates, shall be concentric with the outer edge.
- 6.3 The lettering and spacing shall be uniform and, in the case of circular plates, concentric with the outside edge. For rectangular plates, the lettering shall be parallel with the horizontal edges.
- 6.4 All plate edges shall be finished smooth.
- 6.5 The face side of the nameplate shall have a bright finish.

7. GENERAL REQUIREMENTS

- 7.1 An identification reference corresponding to the valve or cock for which the nameplate is intended shall be permanently marked on the reverse side of each plate when specified by the purchaser.
- 7.2 Nameplates having the inscription in a foreign language shall have the English equivalent indicated on the back of each plate by temporary marking when specified by the purchaser.
- 7.3 Nameplates shall be grouped in sequence according to their identification references, where provided.
- 7.4 The following information shall be supplied by the purchaser while placing order for nameplates:
 - a) The type of nameplate and material,
 - b) Size of nameplate,
 - c) Inscription required,
 - d) Colour of wax filling,
 - e) Valve or cock identification reference number, and
 - f) The number of this standard.
- 7.5 The service nameplates may be secured by screws or by a suitable adhesive, depending on the material of the nameplate.



INDIAN STANDARDS INSTITUTION

Headquarters 1

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110	
Telephones: 331 01 31, 331 13 75 Telegrams: Ma	
(Common to	all offices)
Regional Offices (Telephone
*Western: Manakalaya, E9 MIDC, Marol, Andheri (East), BOMBAY 400093	6 32 92 95
†Eastern : 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola, CALCUTTA 700054	36 24 99
Southern: C. I. T. Campus, MADRAS 600113	41 24 42
Northern: 869 Phase VII, Industrial Focal Point,	8 79 26
S. A. S. NAGAR 160051 (Punjab)	
Branch Offices !	
'Pushpak' Nurmohamed Shaikh Marg, Khanpur,	12 63 48
AHMADABAD 380001	2 63 49
'F' Block Unity Bldg, Narasimharaja Square, BANGALORE 560002	22 48 05
Gangotri Complex, Bhadbhada Road, T. T. Nagar, BHOPAL 462003	6 27 16
22E Kalpana Area, BHUBANESHWAR 751014	5 36 27
5-8-56C L. N. Gupta Marg, HYDERABAD 500001	22 10 83
R14 Yudhister Marg, C Scheme, JAIPUR 302005	6 98 32
-117/418 B Sarvodaya Nagar, KANPUR 208005	4 72 92
Patliputra Industrial Estate, PATNA 800013	6 23 05
Hantex Bldg (2nd Floor), Rly Station Road, TRIVANDRUM 695001	32 27
Inspection Office (With Sale Point):	
Institution of Engineers (India) Building, 1332 Shivaji Nagar PUNE 411005	5 24 35
*Sales Office in Bombay is at Novelty Chambers, Grant Road, Bombay 400007	89 65 28
†Sales Office in Calcutta is at 5 Chowringhee Approach, P O. Princep Street, Calcutta 700072	27 68 00